



# Designer Manufacturer

## AGRO GM

Food-safe protective cabinet - Large Model

*Designed to house a complete computer workstation: monitor, base unit, weighing display, printer and keyboard*

**Characteristics:**

- The body of the cabinet is a single, thermoplastic form, meaning the front and rear structure are a single structure;
- Watertight, smooth surface for easy cleaning;
- The body is an extruded, composite material, 19 mm thick, making it watertight and mechanically strong, preventing condensation build-up and the development of micro-organisms;
- No sharp corners, preventing the build-up of waste/dirt;
- Connectivity: the cabinet is supplied with:
  - A strip of five 220V 10/16A electrical sockets with its own illuminated master switch.
  - Two standard cable glands (7 to 13 mm) to allow cables to enter the cabinet.

**Front panel:**

- Cabinet opening/closed by a shutter blind manufactured using thermoplastic strips and mounted on two PVC rails, fitted with seals to assure the cabinet remains leaktight;
- Two adjustable shelves: one for the monitor and the other for a labelling machine and/or a weighing machine, with the option of sliding shelves (See Option GM 501);
- Joint stop for the reception of the shutter ;
- Sliding polyethylene keyboard shelf;

**Rear panel:**

- Removable rear panel which can be slid down to facilitate access to the computer equipment within.

**Advantages:**

- IP 65 protection and leaktightness
- Optimised working space
- Fully modular internal structure

Also exists in a smaller model: AGRO PM



Joint stop

**AGRO GM DIMENSIONS (mm):**

Overall external	W 880 x D 750 x H 1 000 mm
Usable internal	W 790 x D 600 x H 910 mm

AGRO GM open with keyboard shelf extended



AGRO GM with shutter closed



AGRO GM with GM 501 option



# Fixed and mobile workstations

## DESCRIPTION OF OPTIONS...

The AGRO protection system  
for all your computer equipment

### GM 501 option

- Shelf extension distance: 510 mm;
- Designed for labelling and weighing machines, for the equivalent of a 30kg weight spread across the shelf.
- Telescopic shelf on stainless steel runners with plastic rollers.

### KDL option

- System of opening cable glands, making it possible to connect cables without having to remove their end pieces;
- The cable glands are in two sections which hold the cables in leaktight seals;
- Generally fitted to the right hand side panel, assuring a leaktight cabinet.

### LEGS or WALL MOUNTING option

- Legs in brushed stainless steel (304);
- or
- WALL MOUNTING using brushed stainless steel (304) tubing.

### TOUCH SCREEN INTEGRATION option

- The possibility of integrating a touch sensitive screen.

### Additional options:

- Handle
- Additional shelving;
- PAC GM: Permanent cabinet protection using a transparent PMMA screen behind the sliding blind
  - HC 1: Partial protection of upper or lower compartment;
  - HC 2: Total protection for both compartments;
- Twin, sliding shelf;
- Sloping roof;
- Lock;
- ECA: Heat extraction ventilator;
- IP 66 waterproof mouse and keyboard;
- etc.

