# **Designer Manufacturer**





Protective cabinets for large format thermal printers

General characteristics:

- The body of the cabinet is a single, thermoplastic form, meaning the upper and side panels are a single unit;
- The panels are made of a through-stained, 10 mm thick composite material, protecting the cabinet and making it watertight;
- Smooth and grey outer surface, without angles to facilitate cleaning and avoid the accumulation of waste.
- · Sliding shelf fitted to extending rails, allowing the printer to be removed fully;
- Connectivity: two standard 80 mm cable glands to allow cables to enter the cabinet;

FRONT PANEL :

- Printer controls and labels accessed via the front panel using a 6 mm-thick raisable flap made of PMMA (transparent thermoplastic);
- Blockage the door keeps the PMMA shutter open;
- The raisable flap is closed tightly against the leaktight seals with a latch.

**REAR PANEL :** 

- Shutter filter for heat dissipation ;
- Cable gland diameter 80 mm

## <u>Advantages:</u>

- Ergonomically designed cabinet
- Guaranteed leak-tight seal
- Protection suited to large format thermal printers

### DIMENSIONS OF CIT INDUSTRY (in mm) :

externa

Usable internal

W 450 x D 600 x H 450 mm W 365 x D 570 x H 340 mm



**CIT INDUSTRY with** 

sliding shelf





## Fixed and mobile workstations





**ELEVATION SKIDS option** 





Option

TAV L 12



## The industrial protection solution for your large format laser printers

Option SKIS DE SURÉLÉVATION - ELEVATION SKIDS option

- Two composite material elevation skids fixed to the base to raise the cabinet;
- Facilitates cleaning under the cabinet and avoids stagnant water.

## **KDL** option

- Opening cable gland system designed to allow cables to be connected without having to remove their end pieces;
- The gable glands are in two sections which hold the cables in leaktight seals;
- Generally fitted to the right hand side panel, assuring a leaktight to assure the cabinet remains leaktight.

#### LABEL SLOT options

- LIGHT + GUIDE: Cut-out from the PMMA front panel with a guide to facilitate label handling;
- LIGHT: Cut-out from the PMMA front panel;
- TAV: Inspection port in unbreakable polycarbonate Available in two sizes:
  - TAV L 12: W 220 x H 100 mm watertight; • TAV L 24: W 220 x H 190 mm.

### Additional options:

- Possibility of using 550 mm length slides
- Legs made of brushed stainless steel (304);



