

# Designer Manufacturer

# MODULAR ENERGY CABINET 😡 🐠 🍠









Provides continous power to the mobile workstation's consumers.

#### **Characteristics:**

## • Energy system

- · Capacity batteries: 28 Ah, 40 Ah, 65 Ah
- Battery pack voltage: 24 VDC
- Operating temperatures of between -5 and +35 °C
- The batteries are guaranteed for 300 discharge/recharge cycles.
- Assembly in energy cabinet by LM REALISATIONS
- AGM batteries compatible with all types of transport (land, sea and air);
- Very simple battery replacement procedure;
- Main circuit breaker if the cabinet is not to be used for an extended period;

#### Converter box

· Provides power to multiple consumers (PC, printer, terminal, monitor, etc.) from its multi-voltage outputs, from 5 to 24 V DC and/or 230 V AC;

#### (500 W / 600 W /1500W);

- · Modular, upgradeable cabinet: plug-in, interchangeable converter boards depending on your requirements;
- Safety device to guarantee the service life of the batteries:
- Electronic safety to prevent the battery from being discharged more than 90%;
- The safety is only released when the battery is fully charged;
- Visual alarm (LED) indicating critical levels for autonomy;
- · Main power supply circuit breaker;
- Energy cabinet supplied with installation guide.


#### Battery charger

- Battery charge indicator (two-coloured LED);
- Installed on the charging
- · Mode: Floating/ Boost
- 24V / 5 A 15 A 25 A

### Warranties:

- The manufacturer's warranty is two years (parts and labour), applicable to all component parts used in the cabinet, with the exception of the battery pack;
- The batteries are guaranteed for 300 discharge/recharge cycles.





ENERGY SYSTEM	CONVERTER BOX	CHARGER
• 28 A/h • 40 A/h	<ul> <li>Cabinet with 2 sorties AC 24 V + optional converter board.*</li> <li>Cabinet with 2 sorties AC 24 V + optional converter board.* + 220V 300 W</li> <li>Cabinet with 2 sorties AC 24 V + optional converter board.* + 220V 600 W</li> </ul>	• For 28 A/h • For 40 A/h
• 65 A/h	• Cabinet with 2 sorties AC 24 V + optional converter board.* + 220V 1500 W	• For 65 A/h
	*Converter board 5/12/19/24 V stabilized	1

















